



# TruVis P2026

Product Data Sheet		
<b>PRODUCT/CLASS</b>	Neopentyl glycol dioleate; NPG Polyol Ester	
<b>MANUFACTURING LOCATION</b>	Brownsville, Tennessee	
<b>AVAILABILITY</b>	US. Additional Country Availability information on request.	
<b>MARKET</b>	Industrial, Transportation, Metalworking	
<b>USES/CLAIMS</b>	Base Oil, Additive; Water Miscible Lubricant (Environmentally Friendly)	
<b>APPLICATIONS</b>	Gear, Hydraulic (HFD-U), Grease, 2-Stroke	
<b>PROPERTY</b>		
<b>TYPICAL VALUE</b>	<b>TEST METHOD</b>	
VISCOSITY @ 40°C	26 cSt	ASTM D445-09
VISCOSITY @ 100°C	6.4 cSt	ASTM D445-09
VISCOSITY INDEX	205	
POUR POINT	-30 °C	ASTM D5950-02
FLASH POINT, COC	270 °C	ASTM D92-05A
SPECIFIC GRAVITY @ 20°C	0.903	ASTM D4052-09
COLOR, GARDNER	4	ASTM D6045
ACID VALUE	1.0 mg KOH/g	ASTM D974-08
MOISTURE CONTENT	350 ppm	ASTM E1064-08
SEDIMENT, INSOLUBLE CONTAMINATION	3.5 mg/L	

**Customer Service:**  
1-800-554-9887  
Fax: 401-724-6250



**Teknor Apex Company**  
505 Central Avenue  
Pawtucket, Rhode Island 02861  
[www.teknorapex.com/truvis](http://www.teknorapex.com/truvis)

The information contained herein was obtained on representative samples of the materials and is believed to be reliable. Teknor Apex welcomes an opportunity to discuss your specific requirements regarding sales specifications.