



TruVis P3042

Product Data Sheet		
PRODUCT/CLASS	Glycerol trioleate; Glycerin Ester	
MANUFACTURING LOCATION	Brownsville, Tennessee	
AVAILABILITY	US. Additional Country Availability information on request.	
MARKET	Industrial, Transportation, Metalworking	
USES/CLAIMS	Base Oil, Additive; Water Miscible Lubricant (Environmentally Friendly)	
APPLICATIONS	Gear, Hydraulic (HFD-U), Grease, 2-Stroke	
PROPERTY		
TYPICAL VALUE	TEST METHOD	
VISCOSITY @ 40°C	42 cSt	ASTM D445-09
VISCOSITY @ 100°C	9 cSt	ASTM D445-09
VISCOSITY INDEX	200	
POUR POINT	-20 °C	ASTM D5950-02
FLASH POINT, COC	305 °C	ASTM D92-05A
SPECIFIC GRAVITY @ 20°C	0.919	ASTM D4052-09
COLOR, GARDNER	4	ASTM D6045
ACID VALUE	1.0 mg KOH/g	ASTM D974-08
MOISTURE CONTENT	350 ppm	ASTM E1064-08
SEDIMENT, INSOLUBLE CONTAMINATION	3.5 mg/L	

Customer Service:
1-800-554-9887
Fax: 401-724-6250



Teknor Apex Company
505 Central Avenue
Pawtucket, Rhode Island 02861
www.teknorapex.com/truvis

The information contained herein was obtained on representative samples of the materials and is believed to be reliable. Teknor Apex welcomes an opportunity to discuss your specific requirements regarding sales specifications.