



TruVis P3068

Product Data Sheet		
PRODUCT/CLASS	Modified TMP Trioleate; TMP Complex Ester	
MANUFACTURING LOCATION	Brownsville, Tennessee	
AVAILABILITY	US. Additional Country Availability information on request.	
MARKET	Industrial, Transportation, Metalworking	
USES/CLAIMS	Base Oil, Additive; Water Miscible Lubricant (Environmentally Friendly)	
APPLICATIONS	Gear, Hydraulic (HFD-U), Grease, 2-Stroke	
PROPERTY	TYPICAL VALUE	TEST METHOD
VISCOSITY @ 40°C	68 cSt	ASTM D445-09
VISCOSITY @ 100°C	12.5 cSt	ASTM D445-09
VISCOSITY INDEX	185	
POUR POINT	-40 °C	ASTM D5950-02
FLASH POINT, COC	315 °C	ASTM D92-05A
SPECIFIC GRAVITY @ 20°C	0.930	ASTM D4052-09
COLOR, GARDNER	4	ASTM D6045
ACID VALUE	1.0 mg KOH/g	ASTM D974-08
MOISTURE CONTENT	350 ppm	ASTM E1064-08
SEDIMENT, INSOLUBLE CONTAMINATION	3.5 mg/L	

Customer Service:
 1-800-554-9887
 Fax: 401-724-6250



Teknor Apex Company
 505 Central Avenue
 Pawtucket, Rhode Island 02861
www.teknorapex.com/truvis

The information contained herein was obtained on representative samples of the materials and is believed to be reliable. Teknor Apex welcomes an opportunity to discuss your specific requirements regarding sales specifications.