

APEX® 33043RV-75NT1

Teknor Apex Company - Flexible Polyvinyl Chloride

Saturday, September 14, 2024

| General Information | | | | | | | |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|--------|-------------------------------|--|--|--|
| General | | | | | | | |
| Material Status | Commercial: Active | | | | | | |
| Avoilability | Africa & Middle East | Latin America | | | | | |
| Availability | Asia Pacific | North America | | | | | |
| | ADM Compliant | Ethylene Oxide Steril | izable | | | | |
| Features | • BPA Free | Latex Free | | • Radiation (Gamma) Resistant | | | |
| reatures | DOTP Blend Plasticizer | • Non-Phthalate - TOTM Plasticizer • Radiation Sterilizable | | | | | |
| | E-beam Sterilizable | Non-Phthalate Plasticizer | | | | | |
| Regulatory Statement | Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS. | | | | | | |
| Forms | • Pellets | | | | | | |
| Processing Method | • Extrusion | | | | | | |
| | | | | | | | |
| | ASTM & IS | SO Properties 1 | | | | | |
| Physical | | Nominal Value | Unit | Test Method | | | |
| Density / Specific Gravity | | 1.20 | g/cm³ | ASTM D792 | | | |
| Mechanical | | Nominal Value | Unit | Test Method | | | |
| Tensile Strength | | | | ASTM D638 | | | |
| 50% Strain | | 4.59 | MPa | | | | |
| 100% Strain | | 7.41 | MPa | | | | |
| 300% Strain | | 14.2 | MPa | | | | |
| Tensile Strength (Break) | | 16.8 | MPa | ASTM D638 | | | |
| Tensile Elongation (Break) | | 400 | % | ASTM D638 | | | |
| Hardness | | Nominal Value | Unit | Test Method | | | |
| Durometer Hardness | | | | ASTM D2240 | | | |
| Shore A, 15 sec, Operating Stand | | 69 | | | | | |
| | | 75 | | | | | |

Revision Date: 5/22/2024

APEX® 33043RV-75NT1

Teknor Apex Company - Flexible Polyvinyl Chloride

Additional Information

EXAMPLE EXTRUSION APPLICATIONS

Blood Pressure Tubing

Blood Transport & Delivery

Bubble Tubing

Cable Jacketing

Catheters

Dialysis Tubing

Drainage Tubing

Endotracheal Airway Tubing

Enteral Feeding Systems

Infusion Tubing

Oxygen Tubing

Peristaltic Pump Tubing

Suction Tubing

Data Sheet Applies to Color(s) Listed Below:

Clear NP (1136042) Clear Blue B8 NP (1136669) Clr BluB6NP (1151079)

7/2020-lmo

Processing Information

| 1 rocessing finor mation | | | | |
|--------------------------|--------------------|--|--|--|
| Extrusion | Nominal Value Unit | | | |
| Melt Temperature | 166 to 177 °C | | | |

Notes

¹ Typical properties: these are not to be construed as specifications.

| Teknor Apex Company Corporate Headquarters | Teknor Apex B.V. | Teknor Apex (Suzhou) Advanced Polymer Compounds Co. Pte. Ltd. | Teknor Apex Asia Pacific PTE. LTD. |
|----------------------------------------------------------------|--------------------------------------------|---------------------------------------------------------------|------------------------------------|
| In U.S. for Vinyls, TPEs, Colorants, | Brightlands Chemelot Campus Umonderbaan 22 | No. 78 Ping Sheng Road | 41 Shipyard Road |
| Engineered Thermoplastics (Chem Polymer) 505 Central Avenue | 6167 RD Geleen, Netherlands | Suzhou Industrial Park Jiangsu, China 215126 | Singapore 628134 |
| Pawtucket, Rhode Island 02861 U.S. | Phone: +31 46 7020 950 | | Phone: (65) 6265-2544 |
| | Fax: +31 46 7020 990 | Phone: (86) 512-6287-1550 | Fax: (65) 6265-1821 |
| Phone: 401-725-8000 | | Fax: (86) 512-6288-8371 | |
| Fax: 401-725-8095 | www.teknorapex.com | | www.teknorapex.com |
| Toll Free (U.S. only) 800-556-3864 | tpe@teknorapex.com | www.teknorapex.com infotaap@teknoapex.com | infotaap@teknorapex.com |

www.teknorapex.com info@teknorapex.com

Revision Date: 5/22/2024