

APEX® 33033RV-55NT1 CBL B8 NP

Teknor Apex Company - Flexible Polyvinyl Chloride

Saturday, September 14, 2024

General Information					
General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	 Latin America North America			
Features	ADM CompliantBPA FreeE-beam Sterilizable	Ethylene Oxide SterilizableLatex FreeNon-Phthalate - TOTM Plasticiz	Non-Phthalate Plasticizer Radiation (Gamma) Resistant zer Radiation Sterilizable		
Regulatory Statement	 Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS. 				
Forms	• Pellets				
Processing Method	• Extrusion				

ASTM & ISO Properties 1				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.14	g/cm³	ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength			ASTM D638	
50% Strain	1.72	MPa		
100% Strain	2.93	MPa		
300% Strain	6.65	MPa		
Tensile Strength (Break)	8.62	MPa	ASTM D638	
Tensile Elongation (Break)	430	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness			ASTM D2240	
Shore A, 15 sec, Operating Stand	49			
Shore A, 15 sec, Hand Held	55			

Additional Information

EXAMPLE EXTRUSION APPLICATIONS

Blood Pressure Tubing

Blood Transport & Delivery

Bubble Tubing

Cable Jacketing

Catheters

Dialysis Tubing

Drainage Tubing

Endotracheal Airway Tubing

Enteral Feeding Systems

Infusion Tubing

Oxygen Tubing

Peristaltic Pump Tubing

Suction Tubing

Data Sheet Applies to Color(s) Listed Below:

Clear Blue B8 NP (1136594)

10/19 Core

8/2021: sp

Revision Date: 5/22/2024

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

APEX® 33033RV-55NT1 CBL B8 NP

Teknor Apex Company - Flexible Polyvinyl Chloride

Processing Information

Extrusion Nominal Value Unit

Melt Temperature 154 to 166 °C

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex B.V.	Teknor Apex (Suzhou) Advanced Polymer Compounds Co. Pte. Ltd.	Teknor Apex Asia Pacific PTE. LTD.
In U.S. for Vinyls, TPEs, Colorants,	Brightlands Chemelot Campus Umonderbaan 22	No. 78 Ping Sheng Road	41 Shipyard Road
Engineered Thermoplastics (Chem Polymer) 505 Central Avenue	6167 RD Geleen, Netherlands	Suzhou Industrial Park Jiangsu, China 215126	Singapore 628134
Pawtucket, Rhode Island 02861 U.S.	Phone: +31 46 7020 950		Phone: (65) 6265-2544
	Fax: +31 46 7020 990	Phone: (86) 512-6287-1550	Fax: (65) 6265-1821
Phone: 401-725-8000		Fax: (86) 512-6288-8371	
Fax: 401-725-8095	www.teknorapex.com		www.teknorapex.com
Toll Free (U.S. only) 800-556-3864	tpe@teknorapex.com	www.teknorapex.com infotaap@teknoapex.com	infotaap@teknorapex.com

www.teknorapex.com info@teknorapex.com