

# APEX® 33033RV-65NT1

## Teknor Apex Company - Flexible Polyvinyl Chloride

Saturday, September 14, 2024

General Information					
General					
Material Status	Commercial: Active				
Availability	Africa & Middle East	Latin America			
	<ul> <li>Asia Pacific</li> </ul>	<ul> <li>North America</li> </ul>			
Features	ADM Compliant	Ethylene Oxide Sterilizable	Non-Phthalate Plasticizer		
	• BPA Free	<ul> <li>Latex Free</li> </ul>	• Radiation (Gamma) Resistant		
	• E-beam Sterilizable	<ul> <li>Non-Phthalate - TOTM Plasticize</li> </ul>	er • Radiation Sterilizable		
Regulatory Statement		to regulations, specifically, California Proport r Apex for the most up to date compliance s			
Forms	• Pellets				

ASTM & ISO Properties 1				
Nominal Value	e Unit	Test Method		
1.17	7 g/cm <sup>3</sup>	ASTM D792		
Nominal Value	e Unit	Test Method		
		ASTM D638		
2.76	6 MPa			
4.69	9 MPa			
9.83	3 MPa			
12.4	4 MPa	ASTM D638		
410	0 %	ASTM D638		
Nominal Value	e Unit	Test Method		
		ASTM D2240		
60	0			
65	5			
		65		

#### Additional Information

EXAMPLE EXTRUSION APPLICATIONS

Blood Pressure Tubing

Blood Transport & Delivery

**Bubble Tubing** 

Cable Jacketing

Catheters

Dialysis Tubing

Drainage Tubing

Endotracheal Airway Tubing

Enteral Feeding Systems

Infusion Tubing

Oxygen Tubing

Peristaltic Pump Tubing

Suction Tubing

Data Sheet Applies to Color(s) Listed Below:

CBL B8 NP (1136592)

Clear NP (1136150)

12/20 SP

Revision Date: 5/22/2024

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

## **APEX® 33033RV-65NT1**

## Teknor Apex Company - Flexible Polyvinyl Chloride

#### **Processing Information**

Extrusion	Nominal Value Unit	
Melt Temperature	160 to 171 °C	

#### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex B.V.	Teknor Apex (Suzhou) Advanced Polymer Compounds Co. Pte. Ltd.	Teknor Apex Asia Pacific PTE. LTD.
In U.S. for Vinyls, TPEs, Colorants,	Brightlands Chemelot Campus Umonderbaan 22	No. 78 Ping Sheng Road	41 Shipyard Road
Engineered Thermoplastics (Chem Polymer) 505 Central Avenue	6167 RD Geleen, Netherlands	Suzhou Industrial Park Jiangsu, China 215126	Singapore 628134
Pawtucket, Rhode Island 02861 U.S.	Phone: +31 46 7020 950		Phone: (65) 6265-2544
	Fax: +31 46 7020 990	Phone: (86) 512-6287-1550	Fax: (65) 6265-1821
Phone: 401-725-8000		Fax: (86) 512-6288-8371	
Fax: 401-725-8095	www.teknorapex.com		www.teknorapex.com
Toll Free (U.S. only) 800-556-3864	tpe@teknorapex.com	www.teknorapex.com infotaap@teknoapex.com	infotaap@teknorapex.com

www.teknorapex.com info@teknorapex.com