

APEX® 33033RV-90NT1

Teknor Apex Company - Flexible Polyvinyl Chloride

Saturday, September 14, 2024

General Information				
General				
Material Status	Commercial: Active			
Availability	Africa & Middle East	Latin America		
	 Asia Pacific 	North America		
Features	ADM Compliant	Ethylene Oxide Sterilizable	Non-Phthalate Plasticizer	
	• BPA Free	 Latex Free 	• Radiation (Gamma) Resistant	
	• E-beam Sterilizable	Non-Phthalate - TOTM Plasticis	zer • Radiation Sterilizable	
Regulatory Statement	 Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS. 			
Forms	• Pellets			
Processing Method	• Extrusion			

Nominal Value		Test Method
1.24	g/cm ³	
	g/cm	ASTM D792
Nominal Value	Unit	Test Method
		ASTM D638
10.3	MPa	
13.9	MPa	
19.5	MPa	
20.0	MPa	ASTM D638
360	%	ASTM D638
Nominal Value	Unit	Test Method
		ASTM D2240
85		
90		
	10.3 13.9 19.5 20.0 360 Nominal Value	

Additional Information

EXAMPLE EXTRUSION APPLICATIONS

Blood Pressure Tubing

Blood Transport & Delivery

Bubble Tubing

Cable Jacketing

Catheters

Dialysis Tubing

Drainage Tubing

Endotracheal Airway Tubing

Enteral Feeding Systems

Infusion Tubing

Oxygen Tubing

Peristaltic Pump Tubing

Suction Tubing

Data Sheet Applies to Color(s) Listed Below:

Clear Blue B8 NP (1136587)

Clear NP (1136161)

Trans YW108 (1146696)

4/2021: SP

Revision Date: 5/22/2024

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

APEX® 33033RV-90NT1

Teknor Apex Company - Flexible Polyvinyl Chloride

Processing Information

Extrusion Nominal Value Unit

Melt Temperature 174 to 185 °C

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex B.V.	Teknor Apex (Suzhou) Advanced Polymer Compounds Co. Pte. Ltd.	Teknor Apex Asia Pacific PTE. LTD.
In U.S. for Vinyls, TPEs, Colorants,	Brightlands Chemelot Campus Umonderbaan 22	No. 78 Ping Sheng Road	41 Shipyard Road
Engineered Thermoplastics (Chem Polymer) 505 Central Avenue	6167 RD Geleen, Netherlands	Suzhou Industrial Park Jiangsu, China 215126	Singapore 628134
Pawtucket, Rhode Island 02861 U.S.	Phone: +31 46 7020 950		Phone: (65) 6265-2544
	Fax: +31 46 7020 990	Phone: (86) 512-6287-1550	Fax: (65) 6265-1821
Phone: 401-725-8000		Fax: (86) 512-6288-8371	
Fax: 401-725-8095	www.teknorapex.com		www.teknorapex.com
Toll Free (U.S. only) 800-556-3864	tpe@teknorapex.com	www.teknorapex.com infotaap@teknoapex.com	infotaap@teknorapex.com
www.teknorapex.com			

info@teknorapex.com