

APEX® 32042RV-65NT CBL B8 NP

Teknor Apex Company - Flexible Polyvinyl Chloride

Saturday, September 14, 2024

General Information				
General				
Material Status	Commercial: Active			
Availability	Africa & Middle East	Latin America		
	Asia Pacific	North America		
Features	ADM Compliant	Ethylene Oxide Sterilizable		
	BPA Free	Latex Free Radiatio	n (Gamma) Resistant	
	 DOTP Blend Plasticizer 	Non-Phthalate - Citrate Plasticizer Radiatio	n Sterilizable	
	E-beam Sterilizable	Non-Phthalate Plasticizer		
	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and			
Regulatory Statement	RoHS, please contact Teknor product SDS.	Apex for the most up to date compliance statement, or re	efer to section 15 of the	
Forms	• Pellets			
Processing Method	Injection Molding			

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.19	g/cm ³	ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength			ASTM D638	
50% Strain	2.93	MPa		
100% Strain	4.83	MPa		
300% Strain	9.65	MPa		
Tensile Strength (Break)	13.1	MPa	ASTM D638	
Tensile Elongation (Break)	420	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness			ASTM D2240	
Shore A, 15 sec, Operating Stand	60			
Shore A, 15 sec, Hand Held	65			

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

APEX® 32042RV-65NT CBL B8 NP Teknor Apex Company - Flexible Polyvinyl Chloride

Additional Information

EXAMPLE INJECTION MOLDING APPLICATIONS Adaptors Blood Pressure Bulbs Canulae Caps Connectors Drip/Sight Chambers Ear Protection Endotracheal Airway Cuffs Luers Mouthpieces Oxygen Masks Personal Safety Goggles Resuscitation Bags Suction Bulbs Syringe Bulbs Valves Data Sheet Applies to Color(s) Listed Below: Clear Blue B8 NP (1136675)

10/19 Core

Processing Information			
Extrusion	Nominal Value Unit		
Melt Temperature	163 to 174 °C		

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex B.V.	Teknor Apex (Suzhou) Advanced Polymer Compounds Co. Pte. Ltd.	Teknor Apex Asia Pacific PTE. LTD.	
In U.S. for Vinyls, TPEs, Colorants,	Brightlands Chemelot Campus Umonderbaan 22	No. 78 Ping Sheng Road	41 Shipyard Road	
Engineered Thermoplastics (Chem Polymer)	6167 RD Geleen, Netherlands	Suzhou Industrial Park	Singapore 628134	
505 Central Avenue		Jiangsu, China 215126		
Pawtucket, Rhode Island 02861 U.S.	Phone: +31 46 7020 950		Phone: (65) 6265-2544	
	Fax: +31 46 7020 990	Phone: (86) 512-6287-1550	Fax: (65) 6265-1821	
Phone: 401-725-8000		Fax: (86) 512-6288-8371		
Fax: 401-725-8095	www.teknorapex.com		www.teknorapex.com	
Toll Free (U.S. only) 800-556-3864	tpe@teknorapex.com	www.teknorapex.com	infotaap@teknorapex.com	
		infotaap@teknoapex.com		
www.teknorapex.com				
info@teknorapex.com				

Revision Date: 5/22/2024

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.