

# APEX® 32033RV-55NT1 CBL B8 NP

## Teknor Apex Company - Flexible Polyvinyl Chloride

Saturday, September 14, 2024

General Information						
General						
Material Status	Commercial: Active					
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li> Latin America</li><li> North America</li></ul>				
Features	<ul><li>ADM Compliant</li><li>BPA Free</li><li>E-beam Sterilizable</li></ul>	<ul><li>Ethylene Oxide Sterili</li><li>Latex Free</li><li>Non-Phthalate - TOTM</li></ul>		<ul> <li>Non-Phthalate Plasticizer</li> <li>Radiation (Gamma) Resistant</li> <li>Radiation Sterilizable</li> </ul>		
Regulatory Statement	<ul> <li>Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.</li> </ul>					
Forms	• Pellets					
Processing Method	Injection Molding					
	ASTM & I	SO Properties 1				
Physical		Nominal Value	Unit	Test Method		
Density / Specific Gravity		1.14	g/cm³	ASTM D792		
Mechanical		Nominal Value	Unit	Test Method		
Tensile Strength				ASTM D638		
50% Strain		1.65	MPa			
100% Strain		2.93	MPa			
300% Strain		7.03	MPa			
Tensile Strength (Break)		9.10	MPa	ASTM D638		
Tensile Elongation (Break)		430	%	ASTM D638		
Hardness		Nominal Value	Unit	Test Method		
Durometer Hardness				ASTM D2240		
Shore A, 15 sec, Operating Stand		50				
Shore A, 15 sec, Hand Held		55				

Revision Date: 5/22/2024

## **APEX® 32033RV-55NT1 CBL B8 NP**

### Teknor Apex Company - Flexible Polyvinyl Chloride

#### **Additional Information**

EXAMPLE INJECTION MOLDING APPLICATIONS

Adaptors

Blood Pressure Bulbs

Canulae

Caps

Connectors

Drip/Sight Chambers

Ear Protection

**Endotracheal Airway Cuffs** 

Luers

Mouthpieces

Oxygen Masks

Personal Safety Goggles

Resuscitation Bags

Suction Bulbs

Syringe Bulbs

Valves

Data Sheet Applies to Color(s) Listed Below:

Clear Blue B8 NP (1136779)

10/19 Core

#### **Processing Information**

1 Toccssing Tinot mation				
Extrusion	Nominal Value Unit			
Melt Temperature	157 to 168 °C			

#### Notes

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex B.V.	Teknor Apex (Suzhou) Advanced Polymer Compounds Co. Pte. Ltd.	Teknor Apex Asia Pacific PTE. LTD.
In U.S. for Vinyls, TPEs, Colorants,	Brightlands Chemelot Campus Umonderbaan 22	No. 78 Ping Sheng Road	41 Shipyard Road
Engineered Thermoplastics (Chem Polymer) 505 Central Avenue	6167 RD Geleen, Netherlands	Suzhou Industrial Park Jiangsu, China 215126	Singapore 628134
Pawtucket, Rhode Island 02861 U.S.	Phone: +31 46 7020 950		Phone: (65) 6265-2544
	Fax: +31 46 7020 990	Phone: (86) 512-6287-1550	Fax: (65) 6265-1821
Phone: 401-725-8000		Fax: (86) 512-6288-8371	
Fax: 401-725-8095	www.teknorapex.com		www.teknorapex.com
Toll Free (U.S. only) 800-556-3864	tpe@teknorapex.com	www.teknorapex.com infotaap@teknoapex.com	infotaap@teknorapex.com

www.teknorapex.com info@teknorapex.com

Revision Date: 5/22/2024