

# Halguard® 58130

Teknor Apex Company - Polyolefin

Saturday, September 14, 2024

## General Information

### General

Material Status	• Commercial: Active		
Availability	• Africa & Middle East • Asia Pacific	• Latin America • North America	
Features	• Electrically Insulating • Filled • Flame Retardant	• Good Electrical Properties • Halogen Free • Low Smoke Emission	• Sunlight Resistant (720 hours) • UV Stabilized
Uses	• LSZH Insulation	• LSZH Jacketing	
Agency Ratings	• UL 94		
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.		
Appearance	• Black	• Colors Available	• Natural Color
Forms	• Pellets		
Processing Method	• Wire & Cable Extrusion		

## ASTM & ISO Properties<sup>1</sup>

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.50	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/20.0 kg)	5.9	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	15.0	MPa	ASTM D638
Tensile Elongation (Break)	200	%	ASTM D638
Flexural Modulus	154	MPa	ASTM D790
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D, 10 sec, Operating Stand)	42		ASTM D2240
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	105	°C	ASTM D794
Brittleness Temperature	-52.0	°C	ASTM D746
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity			ASTM D257
23°C	1.2E+16	ohms·cm	
50°C	1.2E+15	ohms·cm	
Dielectric Constant (1 MHz)	3.22		ASTM D150
Dissipation Factor (1 MHz)	0.022		ASTM D150
Flammability	Nominal Value	Unit	Test Method
Flame Rating (3.2 mm)	V-0		UL 94
Oxygen Index	37	%	ASTM D2863

Revision Date: 5/22/2024

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

# Halguard® 58130

## Teknor Apex Company - Polyolefin

### Additional Information

Cone Calorimetry at 75 kW/m<sup>2</sup> ..... ISO-5660

-Peak Heat Release Rate, kW/m<sup>2</sup>: 136

-Total Smoke Released, m<sup>2</sup>/m<sup>2</sup>: 712

-Average Specific Extinction Area, M<sup>2</sup>/kg: 130

Acid Gas Emission

-Halogen Acid Gas Content, %: <0.5% ..... IEC 60754-1

-pH: >/- 4.3 ..... IEC 60754-2

-Conductivity, uS/mm: </-10 ..... IEC 60754-2

Deformation at 121C, % (0.060" thick specimens): 3.2% ..... UL1581

Sunlight Resistance (0.20" thick specimens): Pass ..... UL-1581

Designed for use in non-halogen thermoplastic cable jackets for the New York Transit Authority (NYCTA) Telecommunications Wire and Cable Specific, Specification TC, Issue 7

Data Sheet Applies to Colors Listed Below:

Natural (1070339)

Black 1 (1070448)

11/21-1c

### Processing Information

Extrusion	Nominal Value	Unit
Melt Temperature	204	°C

### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

#### Teknor Apex Company Corporate Headquarters

*In U.S. for Vinyls, TPEs, Colorants,*

*Engineered Thermoplastics (Chem Polymer)*

505 Central Avenue  
Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000

Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

[www.teknorapex.com](http://www.teknorapex.com)

[info@teknorapex.com](mailto:info@teknorapex.com)

#### Teknor Apex B.V.

Brightlands Chemelot Campus Umonderbaan  
22

6167 RD Geleen, Netherlands

Phone: +31 46 7020 950

Fax: +31 46 7020 990

[www.teknorapex.com](http://www.teknorapex.com)

[tpe@teknorapex.com](mailto:tpe@teknorapex.com)

#### Teknor Apex (Suzhou) Advanced Polymer Compounds Co. Pte. Ltd.

No. 78 Ping Sheng Road

Suzhou Industrial Park  
Jiangsu, China 215126

Phone: (86) 512-6287-1550

Fax: (86) 512-6288-8371

[www.teknorapex.com](http://www.teknorapex.com)

[infotaap@teknorapex.com](mailto:infotaap@teknorapex.com)

#### Teknor Apex Asia Pacific PTE. LTD.

41 Shipyard Road

Singapore 628134

Phone: (65) 6265-2544

Fax: (65) 6265-1821

[www.teknorapex.com](http://www.teknorapex.com)

[infotaap@teknorapex.com](mailto:infotaap@teknorapex.com)

Revision Date: 5/22/2024

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no warranties for the products described.