

APEX® 60007 Teknor Apex Company - Flexible Polyvinyl Chloride

Saturday, September 14, 2024

General Information						
General						
Material Status	Commercial: Active					
Availability	 Africa & Middle East Asia Pacific	Latin AmericaNorth America				
Features	Flame Retardant	 Plasticized 				
Uses	Optical Cable Insulation					
Wire Types	• OFN	• OFNR				
Agency Ratings	• UL 1666	• UL 444	• UL VW-1			
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.					
Appearance	Colors Available	Opaque				
Forms	• Pellets					
Processing Method	Wire & Cable Extrusion					

ASTM & ISO Properties ¹						
Physical	Nominal Value	Unit	Test Method			
Density / Specific Gravity	1.49	g/cm ³	ASTM D792			
Mechanical	Nominal Value	Unit	Test Method			
Tensile Strength (Break)	12.1	MPa	ASTM D638			
Tensile Elongation (Break)	300	%	ASTM D638			
Hardness	Nominal Value	Unit	Test Method			
Durometer Hardness (Shore A, 15 sec, Hand Held)	89		ASTM D2240			
Thermal	Nominal Value	Unit	Test Method			
Continuous Use Temperature	90.0	°C	ASTM D794			
Brittleness Temperature	-29.0	°C	ASTM D746			
Flammability	Nominal Value	Unit	Test Method			
Oxygen Index	29	%	ASTM D2863			
Additional Information						

Data sheet Applies to Color Listed Below: Natural (1072338)

10/19-lc

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex B.V.	Teknor Apex (Suzhou) Advanced Polymer Compounds Co. Pte. Ltd.	Teknor Apex Asia Pacific PTE. LTD.
In U.S. for Vinyls, TPEs, Colorants,	Brightlands Chemelot Campus Umonderbaan 22	No. 78 Ping Sheng Road	41 Shipyard Road
Engineered Thermoplastics (Chem Polymer)	6167 RD Geleen, Netherlands	Suzhou Industrial Park	Singapore 628134
505 Central Avenue		Jiangsu, China 215126	
Pawtucket, Rhode Island 02861 U.S.	Phone: +31 46 7020 950		Phone: (65) 6265-2544
	Fax: +31 46 7020 990	Phone: (86) 512-6287-1550	Fax: (65) 6265-1821
Phone: 401-725-8000		Fax: (86) 512-6288-8371	
Fax: 401-725-8095	www.teknorapex.com		www.teknorapex.com
Toll Free (U.S. only) 800-556-3864	tpe@teknorapex.com	www.teknorapex.com	infotaap@teknorapex.com
		infotaap@teknoapex.com	
www.teknorapex.com			
info@teknorapex.com			Povision Data: 5/22/2024

Revision Date: 5/22/2024

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.