🚸 TEKNOR APEX

FIREGUARD® 910-NL1. Teknor Apex Company - Flexible Polyvinyl Chloride

Saturday, September 14, 2024

	General I	nformation		
General				
Material Status	Commercial: Active			
Availability	Africa & Middle East	Latin America		
	Asia Pacific	North America		
Features	Flame Retardant	Low Smoke Emission	l	
Uses	Insulation, Plenum Cable	Plenum Cable Jacketi	ng	
Agency Ratings	• UL 13	• UL 444		
	• UL 1424	• UL QMTM2		
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.			
Appearance	Colors Available	• Opaque		
Forms	• Pellets			
Processing Method	• Wire & Cable Extrusion			
	ASTM & IS	O Properties ¹		
hysical		Nominal Value	Unit	Test Method
Density / Specific Gravity		1.59	g/cm ³	ASTM D792
Iechanical		Nominal Value	Unit	Test Method
Tensile Strength (Break)		16.5	MPa	ASTM D638
Tensile Elongation (Break)		250	%	ASTM D638
lardness		Nominal Value	Unit	Test Method
Durometer Hardness (Shore C, 10 sec, Hand Held)		85		ASTM D2240
hermal		Nominal Value	Unit	Test Method
Continuous Use Temperature		75.0	°C	ASTM D794
Brittleness Temperature		-11.0	°C	ASTM D746
lectrical		Nominal Value	Unit	Test Method
Dielectric Strength		33	kV/mm	ASTM D149
Dielectric Constant				ASTM D150
1 kHz		4.67		
1 MHz		3.62		
Dissipation Factor				ASTM D150
1 kHz		0.080		
1 MHz		0.035		
lammability		Nominal Value	Unit	Test Method
Oxygen Index		46	%	ASTM D2863

Revision Date: 5/22/2024

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

Copyright © 2024 UL Prospector

FIREGUARD® 910-NL1. Teknor Apex Company - Flexible Polyvinyl Chloride

Additional Information

Dynamic Thermal Stability @ 190°C, 80 RPM, #5 Bowl (Mins. To Decomposition) : 42..... ASTM D2538

Kayeness ACR @ 350°F, 1000 sec-1 (Pa-sec) : 302..... ASTM D3835

Cone Calorimeter @ 75 kW/m2 ISO5660 Peak Heat Release Rate (kW/m^2) : 120 Average Heat Release Rate (kW/m^2) : 72 Total Heat Released (MJ/m^2) : 75 Average Heat of Combustion (MJ/kg): 12.1 Average Specific Extinction Area (m^2/kg) : 259 Peak Smoke (1/m): 1.58

Data Sheet Applies to Colors Listed Below: Natural (0131252) Blue 2072 (1049170) Yellow 731 (1057819)

10/19-lc

Processing Information				
Extrusion	Nominal Value Unit			
Melt Temperature	196 °C			

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex B.V.	Teknor Apex (Suzhou) Advanced Polymer Compounds Co. Pte. Ltd.	Teknor Apex Asia Pacific PTE. LTD.
In U.S. for Vinyls, TPEs, Colorants,	Brightlands Chemelot Campus Umonderbaan 22	No. 78 Ping Sheng Road	41 Shipyard Road
Engineered Thermoplastics (Chem Polymer) 505 Central Avenue	6167 RD Geleen, Netherlands	Suzhou Industrial Park Jiangsu, China 215126	Singapore 628134
Pawtucket, Rhode Island 02861 U.S.	Phone: +31 46 7020 950		Phone: (65) 6265-2544
	Fax: +31 46 7020 990	Phone: (86) 512-6287-1550	Fax: (65) 6265-1821
Phone: 401-725-8000		Fax: (86) 512-6288-8371	
Fax: 401-725-8095	www.teknorapex.com		www.teknorapex.com
Toll Free (U.S. only) 800-556-3864	tpe@teknorapex.com	www.teknorapex.com infotaap@teknoapex.com	infotaap@teknorapex.com
www.teknorapex.com			
info@teknorapex.com			

Revision Date: 5/22/2024

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.